



	Supply air valve Zehnder ComfoValve Luna S	Extract air valve Zehnder ComfoValve Luna E
Valve type	Supply air valve	Extract air valve
Material	Plastic	Plastic
Colour	White similar to RAL 9003	White similar to RAL 9003
Application	Up to 75 m <sup>3</sup> /h Up to 45 m <sup>3</sup> /h	Up to 75 m <sup>3</sup> /h Up to 45 m <sup>3</sup> /h
Operating temperature	Up to 60 °C	Up to 60 °C
<b>Dimensions and weight</b>		
Dimensions	170 x 170 x 70 mm	170 x 170 x 102 mm
Design	Round	Round
Diameter	170 mm	170 mm
Installation height regardless of setting	30 mm	30 mm
Weight	0.280 kg	0.320 kg
Undercut	Maximum 5 mm	Maximum 5 mm
<b>Installation</b>		
Installation	Fast, simple, no tools required	Fast, simple, no tools required
Installation location	Wall and ceiling	Wall and ceiling
Connection dimension	DN 125	DN 125
Airtight installation	✓ with rubber seal	✓ with rubber seal
<b>Adjustment</b>		
Precise and easy adjustment	✓	✓
Air flow setting	25 adjustment positions	75 adjustment positions
Flow setting scale	0-25	0-25
Levels	1 level	3 levels
Locking mechanism for air flow setting	✓	✓
Documentation of air flow setting	Documentation fields on the inside of the valve	Documentation fields on the back of the valve
<b>Special features</b>		
Outflow / suction area	360° 240° limitable with AirBlocker	360°
Coanda effect	Optimised outflow area for silent and draught-free air supply	-
Filter	-	Filter to protect the ventilation tubes against dirt Article number: 990 320 031
Appearance / design	Perfectly harmonised design Consistent appearance for perfect combination in spaces with supply and extract air terminals	
Discreet integration into any living space	✓ Clear design and minimum installation height of 30 mm regardless of the air flow setting	
UV-resistant	✓	✓
Colourfast	✓	✓
Scratch-resistant	✓	✓
Easy to clean	✓	✓